

Win-win Cooperation



#### **DONGGUAN TINOK PRECISION CERAMICS CO., LTD**

Web.: www.tinokceramics.com Add.: Tai'an Road, Chang'an Town, Dongguan City 523867, China

# 2024 Company Profile

About Us | Manufacturing Facilities | Products | Materials & Application

PRECISION CERAMICS MANUFACTURER

Contact: Tina Wu Mobile: +86-13580880042 Email: tina@tinokceramics.com

Based products Create quality products





### 目录 / CONTENTS







TINOK Precision Ceramics was established in 2016, located in Dongguan city, China. It's a professional factory of producing precision ceramic (Zirconia, Alumina, Si3N4, SiC) products that serving both domestic and overseas customers.

The company offers one to stop service, from forming, sintering, processing and inspection, mainly accepting customization based on drawings and samples. The precision ceramic products we produce are widely used in industries such as photovoltaic & new energy, semiconductors, medical & food, measuring tools, electronic appliances, petroleum & mining, military, aerospace, etc., to meet the diverse needs of customers.

TINOK Ceramics has a complete set of production equipment, such as molding equipment: isostatic pressing molding machine, dry pressing molding machine, injection molding machine; Sintering furnace; Processing equipment: flat grinding, centerless grinding, internal cylindrical grinding, external cylindrical grinding, internal & external cylindrical grinding, honing, punching, CNC machining center, etc.

In addition, the company obtained ISO 9001-2015 quality system certification and independent import-export license.

## **生产设备** Manufacturing Facilities



### workshopdisplay 车间展示 ⊿











**B**R-Grinding













### 加工设备清单 LIST OF PROCESSING EQUIPMENT

序号 No.	<b>设备名称</b> Name	名間題 Total Oly	RE City	構度 Precision	品牌 Brand	<b>世号</b> Type	7418 Placenforgn	最大行程(mm) Max stoke(mm
1	无心磨床 Centerless Grinder	6pcs	6pcs	0.003	健和 Jorte	JHC*12S	Taiwan	ø60*800
2	<b>平面慶床</b> Surface Grinding Machine	15PCS	12PCS	0.002	開光 Shujuang	SGM*450	China	450*150*300
3			3PCS	0.002	<b>网本</b> Okamoto	ACC35011	Japan	
4	神子机 Pin-lap Grinding Machune	13PCS	13PCS	0.002	正佳 Zhengia	WE6800*2	China	ø50*80
5	数控车床 CNC Lathe	3PCS	2PCS	0.01	广中数控	VIVA T2C*500	China	ø280*200
6			1PCS	0.005	马扎克 MAZAK	QTE-100L	Japan	e180*100
7	成上车床 Table Lathe	3PCS	3PCS	0.05-0.1	<b>精城</b> Jingcheng	B*25	China	ø25*500
8	CNC高速机 CNC Milling Machine	3pcs	3pcs	0.01	常准	650	TAiwan	650*550*450
9	CNC MILLIA CNC Engraving and Milling Machine	3PCS	3PCS	0.005	北京精雕」の	JDKGT600	China	600*500*250
10	CNC加工中心 CNC Machine	2pcs	2pcs	0.03	台数域 Tazty	TL*860VMC*L	China	800*550*450

### 检测设备清单 TEST EQUIPMENT LIST

Wanhao Projector	2 pcs
Mitutoyo Magnifying Display instrument	1 set
Mitutoyo Micrometer calipers	10 pcs
Mitutoyo Percentile calipers	20 pcs
Mitutoyo Dial indicator	4 pcs
Mitutoyo Micrometer Height Gauge	5 pcs
Nikon Height Gauge	2 pcs
Mitutoyo Outer Diameter Dial meter	10 pcs
Mitutoyo Roughness meter	1 pc
Standard 0.001 ceramic needle gauges 1mm-20mm	1 full set
M2-M20 Standard ceramic gauges	1 full set
1mm-20mm standard 0.001 ceramic ring gauges	1 full set









搬运晶圆片机械手臂 Ceramic arms for carrying wafers 微孔陶瓷吸盘 Microporous ceramic sucker















医疗 & 食品泵 / 阀 Medical & Food pumps / valves








石油 & 采矿 Petroleum & Mining







其他行业 Other Industries



Material & Application



单位Unit

g/cm<sup>3</sup> HV0.5

MPa

MPa


MPa.m12

GPa

10<sup>4</sup>K<sup>1</sup>

AT'C

ΩCM C




### 氧化锆材料特性 Properties of zirconia materials



项目item	数值Data	单位Unit	项目item	数值Data
密度Dansity	6.02	g/cm <sup>3</sup>	密度Density	3.85
显微硬度 Mcrohardness	1200	HV0.5	显微硬度 Microhardness	1600
弯曲硬度 Bending hardness	800	MPa	弯曲硬度 Bending hardness	310
抗压强度 Compressive strength	3000	MPa	抗压强度 Compressive strength	2400
断裂韧性 Fracture toughness	8	MPa.m <sup>1/2</sup>	断裂韧性 Fracture toughness	3-4
弹性模量 ElasticModulus	200	GPa	弹性模量 ElasticModulus	340
热膨胀系数 Coefficient of thermal expansion	10	10'K'	热膨胀系数 Coefficient of thermal expansion	7-8
热震稳定性(水冷却) Thermal shock stability (water cooling)	300	ΔT°C	热震稳定性(水冷却) Thermal shock stability (water cooling)	200
20℃电阻率 The 20℃ resistivity	>1013	ΩCM	20℃电阻率 The 20℃ resistivity	>10 <sup>14</sup>
最高使用温度 Maximum service temperature	1000	C	最高使用温度 Maximum service temperature	1600

















We will prove with our strength that we are the best, let's bravely do it!






We will prove with our strength that we are the best, let's bravely do it!





We are constantly growing and expanding!

Unit : Million(CNY)

















Win-win Cooperation

#### DONGGUAN TINOK PRECISION CERAMICS CO., LTD

Web.: www.tinokceramics.com Add.: Tai'an Road, Chang'an Town, Dongguan City 523867, China

> Based Products Create Quality Products

# 谢谢观看 THANK YOU

Contact: Tina Wu Mobile: +86-13580880042 Email: tina@tinokceramics.com